

# DOUBLE WINDOW TYPE SIGHT FLOW INDICATOR

## MODEL CODE : EKW

These are suitable for Transparent, slightly opaque solutions and it may be used for gases m<sup>2</sup>.

### Special Features :

- Time Proven Design
- Low Cost
- Easy Installation
- Easy Maintenance
- Available in Various Materials

### Applications :

1. Opaque Solutions
2. Gases m<sup>2</sup>
3. Continuous Flow Monitoring in Pipelines

### Specifications :

#### Standard Version :

<b>Process Connection</b>	: Flanged or as per requirement.
<b>Operating Pressure</b>	: Atmospheric to 20 kg/cm <sup>2</sup>
<b>Operating Temperature</b>	: 100°C
<b>Hydrotest Pressure</b>	: 30 kg/cm <sup>2</sup>



## HOW TO ORDER

### BASIC MODEL

Example

EKW

### M.O.C. OF PROCESS CONNECTION

T

C : C.S.    T : SS 316  
S : SS 304    X : NON STANDARD

### PROCESS CONNECTION SIZE

6M

S : SCREWED  
4M : 1/2" NPT (M)      4F : 1/2" NPT (F)  
5M : 3/4" NPT (M)      5F : 3/4" NPT (F)  
6M : 1" NPT (M)        6F : 1" NPT (F)

OR

### FLANGED ANSI B 16.5 - RF

2A

6A : 3/4" 150#      4A : 1 1/2" 150#      7A : 3" 150#  
6B : 3/4" 300#      4B : 1 1/2" 300#      7B : 3" 300#  
6C : 3/4" 600#      4C : 1 1/2" 600#      7C : 3" 600#  
1A : 1" 150#        2A : 2" 150#        9A : 4" 150#  
1B : 1" 300#        2B : 2" 300#        9B : 4" 300#  
1C : 1" 600#        2C : 2" 600#        9C : 4" 600#      X: NON STANDARD

**SIGHT FLOW  
INDICATOR**

# DOUBLE WINDOW TYPE SIGHT FLOW INDICATOR



## **MODEL CODE : EKW**

### **M.O.C. OF BODY**

C : C.S.      T : SS 316  
S : SS 304    X : NON STANDARD

### **M.O.C. OF COVER PLATE**

C : C.S.      T : SS 316  
S : SS 304    X : NON STANDARD

### **M.O.C. OF HARDWARE**

C : C.S.      T : SS 316  
S : SS 304    X : NON STANDARD

### **TYPE OF DOUBLE WINDOW**

A : ROTARY      C : DRIP  
B : FLAPPER    NA : NOT APPLICABLE

### **M.O.C. OF DOUBLE WINDOW TYPE**

C : C.S    S : SS 304    T : SS 316

### **M.O.C. OF GLASS**

T : TOUGHENED GLASS    X : NON STANDARD

### **PACKING**

P : PTFE      T : TEFLON    X : NON STANDARD

### **FINISH**

B : BUFFED    M : MAT      X : NON STANDARD

T

T

T

B

T

T

P

B

**Ordering Example: EKW - T - 6M - OR - 2A - T - T - T - B - T - T - P - B**

FOR OTHER OPTIONAL ITEMS, PLEASE CONTACT FACTORY FOR DELIVERY AND MINIMUM QUANTITY OF ORDER.

Note : Specifications and dimensions given in this product catalogue represents the state of engineering at the time of printing.

Modifications may take place and materials specified may be replaced by others without prior notice.

**SIGHT FLOW  
INDICATOR**